

## All-aluminium moving-floor semitrailer



Keep things moving forward.





Discharge funnel with bracket



Central control panel



Lateral protective tarpaulin



Rear apron with protective flap



Keep things moving forward



LED rear lights



External rod locks



Floor-protection tarpaulin



Hinged rear bow



ulin



Wear panel on sidewall



Brackets for broom and shovel



CARNEHL



Hinged underside guard w. aluminium ladder



Floor with continuous lateral reinforcement



Platform with access from both sides



Bulkhead door



### Computer-aided aluminium manufacturing



Keep things moving forward.

### Technical Data of Moving-Floor Trailer

<b>Weights:</b>	<b>Legally permissible</b>	<b>Technically permissible</b>
Total weight	36,000 kg	43,000 kg
Fifth-wheel load	12,000 kg	16,000 kg
Bogie load	24,000 kg	27,000 kg
Tare weight (Standard*)	7,300 kg	7,300 kg

<b>Dimensions:</b>	
Fifth-wheel height	1,150 mm
Total height	4,000 mm
Loading length	13,500 mm
Loading width	2,480 mm
Wall height	2,700 mm / 2,800 mm
Floor thickness	6* mm / 8 mm / 10 mm
Capacity	92 m <sup>3</sup>